

Heavy Duty Handling Trackless Transfer Trailer

Trackless transfer trailer runs on cement floor or steel plate ground. It has a load ability from 1t to 300t. It is a kind of transfer trailer with simple structure, easy operation, cost-effectiveness price, large start torque and steady start.



The trackless transfer trailer can turn around freely 360 degrees. Its wheels are specially designed so that the trackless transfer cart does no damage to the ground.



Other features:

Heat resistance
Anti-explosion
No limit of running distance
Anti-dust painting
Designed length and width
Narrow or wide rail gauge



Application

The trackless transfer trailer is usually applied in metallurgy plant, coal and mine industry, electronics and Other heavy industries to transfer heavy cargoes of weldments, machine processing pieces, metal forging and casting, melt steels, etc.



www://transfer-cart.com Tel:86 373 5921456 Fax:86 373 3020456 Email:sale@transfer-cart.com



Xinxiang Hundred Percent Electrical & Mechanical Co.,Ltd

Also, a v-bed can be added on the platform to transfer cargoes of special shapes such as steel coils, coiled sheets, galvanized coils, mills, steel tubes and pipes and other heavy cargoes of special shapes in metallurgy plant and shipbuilding industry.



Technical Parameters

| Rated load(t) | 5 | 15 | 30 | 50 |
|------------------------|-------------------------------------|-----------|--------------------|-----------|
| Structure of frame | Steel plates welded, beam structure | | | |
| Thickness of the steel | 8 | 12 | 14 | 16 |
| plate(mm) | | | | |
| Wheel load(t) | 2.8 | 4.3 | 7.7 | 12 |
| Structure of frame | Steel plates welded, beam structure | | | |
| Thickness of the steel | 8 | 12 | 14 | 16 |
| plate(mm) | | | | |
| Wheel load(t) | 2.8 | 4.3 | 7.7 | 12 |
| Ground requirement | Cement ground | | Steel plate ground | |
| Table size(mm) | 3000*2000 | 4000*2200 | 5000*2200 | 6000*2300 |
| Motor power (kw) | 3.5 | 6 | 10 | 15 |
| Wheel | 300/4 | 350/4 | 400/4 | 400/6 500 |
| diameter(mm)/quantity | | | | |
| Wheel quality | Zg55+ hydropur ture | | | |
| Function of charger | Automatic charging | | | |
| motor | | | | |
| Radar control | 3-0.3, automatic stop for obstacles | | | |

If you have some special requirements in table size(length and width),motor power, control method(remote control, hand held pendant control), our engineers could design for you!

www://transfer-cart.com Tel:86 373 5921456 Fax:86 373 3020456 Email:sale@transfer-cart.com